



date	
customer	
project	
quantity	

# SMART LED FLEX Luminaire





SmartLedFlex® is a flexible linear lighting product for both indoor and outdoor (IP66) applications. It is perfect for architectural illumination that provides a high performance homogenous light to highlight the perimeters and outlines of buildings, bridges, etc.

SmartLedFlex® has 100 LEDs/m. SMD Nichia Side View enclosed in special flexible polymer material, which allow the product to be bent into different winding shapes and the product is protected against UV rays thanks to the silicone outer shell.

Available in monochromatic & RGB -and two versions; square and round.



Family	Type	Run length	Color temp / Wattage / Lumens	Driver	Input voltage		
<b>MC-7211</b>		Advise on run length					
 N, A, D  	0	round monicolor	* Max 33' Run -->	<b>70/2K7</b>	2700K 2.93W 47lm/FT	<b>N</b> non dim <b>A</b> 0-10V <b>D</b> DMX	<b>24</b> 24VDC input 120/277V
	1	square monicolor	* Max 33' Run -->	<b>70/3K5</b>	3500K 2.93W 68 lm/FT		
	2	round RGB	* Max 33' Run -->	<b>70/5K2</b>	5200K 2.93W 85 lm/FT		
	3	square RGB	* Max 33' Run -->	<b>11</b>	RGB 3.66W 38 lm/FT		
			* Max 33' Run -->				
			* Max 33' Run -->				
		* Max 33' Run -->					
		** Max 26' Run -->					

example...

Family	Type	Run Length	Color temp / Wattage / Lumens	Driver	Input voltage
MC-7211	0	?	70/3K5	A	24

\* Priced based on 33 ft. run for colored white. Max 33 ft. run per driver.

\*\* Priced based on 26 ft. run for RGB. Max 26 ft. run per driver.

