


Luminaire

PIANO-P

date cust proj qua

e	
tomer	
ect	
ntity	

Pendant-Only luminaire with direct-indirect lighting balanced room ambiance, for light component: approx. direct 50% / indirect 50%, trooping function (communication system between luminaires for light and movement), outstanding ease of maintenance, housing made from aluminum and die-cast zinc, diffuser made from prismatic acrylic glass with side-emitting LEDs (diffuser is completely transparent when switched off), Y-wire-rope suspension 2-fold with height adjustment (length: 59.1in), transparent connecting cable (5-core, prefabricated), ceiling box made from ABS plastic in the same color as the luminaire, LED converter integrated.



Family	Wattag	e / Lumens / I	Length		Mounting	(	Color temp		Beam		Finish		Driver		CRI	Inp	ut voltage
PIANO-P																	
	10A 80W   10B 120V   10C 160V	V >12570lm	55.1in 76.8in 101.3in	Ρ	pendant	30 40	3000K 4000K	S	standard	S W	white	N A C		80	CRI80	120 277	120V input 277V input

example	Family	Wattage / Lumens / Length	Mounting	Color temp	Beam	Finish	Driver	CRI	Input voltage	
	PIANO-P	10A	Р	30	S	S	Α	80	120	

