

date	
customer	
project	
quantity	

HALO LED Ceiling Surface-Mounted

High-class ring LED luminaire, designed for direct light emission, with lamp housing in a compact design made of seamlessly welded steel sheet. 1:1 direct-indirect equal emission of light. Light emission through diffusers made of satined PMMA for an almost homogeneous emission of light. Diffusers direct-indirect with a height of 8mm for lateral emission of light. Luminaire equipped with the latest generation of LEDs, color rendering index Ra > 80, small color tolerance MacAdam 3. Electrical connection through 3 or 5-pin transparent power supply cable and ceiling housing. Optional mounting positions of the ceiling housing: offset or central.



S



Family Diameter / Wattage / Lumens / Beam / IP Rating							Mounting		CCT		Finish		Driver		Input voltage	
HALO																
SURFACE-1 SURFACE-2 SURFACE-3 SURFACE-4	29.9" 40.9" 48.0" 53.5"	41W 51W 62W 74W	>3710lm >4357lm >5591lm >6962lm	dir. dir. dir. dir.	IP20 IP20 IP20 IP20	S	surface	830 840		W S R	white silver RAL color	AC	0-10V consult for options	120 277 UNI	120V input 277V input universal input	
	•							•	Notes: (*)	•					



