


HALO LED Ceiling Surface-Mounted

High-class ring LED luminaire, designed for direct light emission, with lamp housing in a compact design made of seamlessly welded steel sheet. 1:1 direct-indirect equal emission of light. Light emission through diffusers made of satined PMMA for an almost homogeneous emission of light. Diffusers direct-indirect with a height of 8mm for lateral emission of light. Luminaire equipped with the latest generation of LEDs, color rendering index Ra > 80, small color tolerance MacAdam 3. Electrical connection through 3 or 5-pin transparent power supply cable and ceiling housing. Optional mounting positions of the ceiling housing: offset or central.



S



Family		Diameter / Wattage / Lumens / Beam / CCT				Mounting		Finish		Driver		Input voltage		
HALO														
SURFACE-1	29.9"	41W	>3710lm	dir.	3000K	S	surface	W	white	A	0-10V	UNI	universal input	
SURFACE-1	29.9"	41W	>3837lm	dir.	4000K				S B R					silver
SURFACE-2	40.9"	51W	>4357lm	dir.	3000K									black
SURFACE-2	40.9"	51W	>4509lm	dir.	4000K									RAL color
SURFACE-3	48.0"	62W	>5591lm	dir.	3000K									
SURFACE-3	48.0"	62W	>5786lm	dir.	4000K									
SURFACE-4	53.5"	74W	>6962lm	dir.	3000K									
SURFACE-4	53.5"	74W	>7200lm	dir.	4000K									

Notes: (*)

example...	Family	Diameter / Wattage / Lumens / Beam / IP Rating				Mounting	Finish	Driver	Input voltage
	HALO	SURFACE-1				S	W	A	UNI

S
mounting

