




DOWNITO-110 Luminaire



7112

date _____
 customer _____
 project _____
 quantity _____

Downito 110. A new LED downlight multi-power (16 W to 32 W), perfect for general and ambient lighting of retail applications. The design of its active 40° and 70° reflectors, designed by Bartenbach GmbH, allows us to distribute light with unique precision and high performance up to 110 lm/W. Furthermore, this LED downlight offers the possibility of combine 4 types of passive reflectors in different finishes; white, black, aluminum and gold. Design, precision and high performance, the perfect combination for the success of your lighting project.



Family	Model / Wattage	IP Type	Finish	Beam / Lumens	CRI / Color temp	Diffuser	Passive Reflector	Driver	Input voltage
DOWNITO 110									
	7112-16 16W	0 IP20	0 silver	1 40 deg - 1270 - 3160 lm	80/5K 5000K	C *clear	C chrome	N non dim	120 120V input
	7112-20 20W	1 IP40 - Diffuser	2 black	2 70 deg - 1175 - 2923 lm	90/4K 4000K	M *milky	B black	A 0 - 10V	277 277V input
	7112-24 24W	2 IP54 - Diffuser & Gasket	3 white		80/3K5 3500K		W white	N1 non dim	
	7112-28 28W				90/3K 3000K		G gold	A1 0 - 10V	
	7112-32 32W				90/2K7 2700K				



N1, A1



N, A

Notes: (*) IP40 & IP54 only

example...

Family	Model / Wattage	IP Type	Finish	Beam / Lumens	CRI / Color temp	Diffuser	Passive Reflector	Driver	Input Voltage
DOWNITO 110	7112-32	1	0	2	90/4K	C	C	N	120

