







# LICHTKANAL 070

Lighting System (Indoor Ceiling Pendant - IP20)

date	
customer	
project	
quantity	

LICHTKANAL is available in several variations. The diffuser is in form of different acrylic profiles for various lighting tasks. All Lichtkanal sizes are characterized by their continuously illuminated surface. Individual solutions, e.g. wall-ceiling or wall-edge solutions can be designed.

- acrylic diffuser profile with snap-in technique
- highest-quality aluminum profile
- various suspension systems available as accessories

<h3>LK70 Indoor Ceiling Pendant</h3>  <p>Click here for LK45 Indoor Ceiling Pendant</p>	<p>Click here for LK45 Indoor Ceiling Surface</p>  <p>S</p>	<p>Click here for LK45 Indoor Ceiling Recessed</p>  <p>RNTC RNT</p>	<p>Click here for LK45 Indoor Wall Surface</p>  <p>WD</p>	
	<p>Click here for LK70 Indoor Ceiling Surface</p>	<p>Click here for LK70 Indoor Ceiling Recessed</p>	<p>Click here for LK70 Outdoor Ceiling Recessed</p>	<p>Click here for LK70 Indoor Wall Surface</p>
	<p>Click here for LK70 Outdoor Ceiling Surface</p>	<p>Click here for LK70 Outdoor Wall Surface</p>	<p>Click here for LK70 Outdoor Wall Surface</p>	<p>Click here for LK70 Outdoor Wall Surface</p>



example...



Family	Profile size	Mounting	Insert CCT	Performance	Finish	Driver	Input voltage	Run Length in ft.
LK	LK070	PC	40	RO	S	A	U	12

Family	Profile size	Mounting	Insert CCT	Performance	Finish	Driver	Input voltage	*Run Length in ft.																	
LK	LK70	70mm (2.76")	PC	pendant - cables included	27	2700K	RO	7W /1000lm/ft	S	silver	A	0-10V	120	120V											
																30	3000K	HO	11W /1500lm/ft	B	black	E	EM	277	277V
																35	3500K	VHO	15W /2000lm/ft	W	white			U	universal
																40	4000K								

Notes: \*Actual length may be different than nominal length. Request shop drawings prior to placing an order.



### Light Distribution Options For All LK Versions

