Recessed Downlights Fixed LED

Intertek | LED BUILT IN | 80 CRI | 2.67″ | 1.97″ ceiling depth | 120°

D10103T | 3W | SMD LED | *Fixed Recessed Downlight*

IP20



* New Construction Housing Available
Driver Enclosure = 8″ x 10″ x 6″ w/10′ Standard Connecting Cable
Installation Depth = 6.5″

120V Not dimmable,
277V consult for dimming

FAMILY	ITEM#	WATTAGE	LUMENS	CCT	BEAM	FINISH	IP RATING	INPUT VOLTAGE
BUNDT	D10103T	3W	210lm	3000K	120°	WHITE	IP20	120V - 277V

Intertek | LED BUILT IN | 80 CRI | 3.34″ | 2.36″ ceiling depth | 120°

D10107T | 7W | SMD LED | *Fixed Recessed Downlight*

IP20





* New Construction Housing Available
Driver Enclosure = 8″ x 10″ x 6″ w/10′ Standard Connecting Cable
Installation Depth = 6.5″

Consult for dimming

FAMILY	ITEM#	WATTAGE	LUMENS	CCT	BEAM	FINISH	IP RATING	INPUT VOLTAGE
BUNDT	D10107T	7W	520lm	4000K	120°	WHITE	IP20	120V - 277V

Intertek | LED BUILT IN | 80 CRI | 5.11" | 2.36" ceiling depth | 120°

D10115T | 15W | SMD LED | *Recessed Downlight*

IP20



* New Construction Housing Available
Driver Enclosure = 8" x 10" x 6" w/10' Standard Connecting Cable
Installation Depth = 6.5"

0-10V dimming option, available for 277V

FAMILY	ITEM#	WATTAGE	LUMENS	CCT	BEAM	FINISH	DRIVER	IP RATING	INPUT VOLTAGE
BUNDT	D10115T	15W	1050lm	3000K	120°	WHITE	0-10V	IP20	120V - 277V

Intertek | LED BUILT IN | 80 CRI | 8.26" | 2.95" ceiling depth | 120°

D10124T | 24W | SMD LED | *Recessed Downlight*

IP20



Remote Driver Enclosure = 6" x 10" x 2"
w/10' Standard Connecting Cable



0-10V dimming option, available for 277V

FAMILY	ITEM#	WATTAGE	LUMENS	CCT	BEAM	FINISH	DRIVER	IP RATING	INPUT VOLTAGE
BUNDT	D10124T	24W	1800lm	4000K	120°	WHITE	0-10V	IP20	120V - 277V

Intertek | LED BUILT IN | 80 CRI | 2.75" | 2.36" ceiling depth | 100°

D10107UV | 7W | SMD LED | *UGR19 Fixed Recessed Downlight w/ Adjustable CCT*

IP44



* New Construction Housing Available
Driver Enclosure = 8" x 10" x 6" w/10' Standard Connecting Cable
Installation Depth = 6.5"
Consult for dimming



FAMILY	ITEM#	WATTAGE	LIGHT COLOR	CCT	BEAM	LUMENS	FINISH	INPUT VOLTAGE
ENNEN	D10107UVW	7W	Daylight - Cool White - Warm White	6000K - 4000K - 3000K	100°	525lm	WHITE	120V - 277V

FAMILY	ITEM#	WATTAGE	LUMENS	CCT	BEAM	FINISH	DRIVER	IP RATING	INPUT VOLTAGE
DLDR	D10116FDW	16W	800lm	3000K	G	WHITE	0-10V	IP20	120V - 277V
DLDR	D10116FDB	16W	800lm	3000K	G	BLACK	0-10V	IP20	120V - 277V

Intertek | LED BUILT IN | 80 CRI | 4.72" | 2.75" ceiling depth | 100°

D10113UV | 13W | SMD LED | *UGR19 Fixed Recessed Downlight w/ Adjustable CCT*

IP44



* New Construction Housing Available
Driver Enclosure = 8" x 10" x 6" w/10' Standard Connecting Cable
Installation Depth = 6.5"



Consult for dimming

FAMILY	ITEM#	WATTAGE	LIGHT COLOR	CCT	BEAM	LUMENS	FINISH	DRIVER	INPUT VOLTAGE
ENNEN	D10107UVW	13W	Daylight - Cool White - Warm White	6000K - 4000K - 3000K	100°	975lm	WHITE	0-10V	120V - 277V

Intertek | LED BUILT IN | 80 CRI | 6.7" | 2.95" ceiling depth | 100°

D10120UV | 20W | SMD LED | *UGR19 Fixed Recessed Downlight w/ Adjustable CCT*

IP44



Remote Driver Enclosure = 6" x 10" x 2"
w/10' Standard Connecting Cable



0-10V dimming option, available for 277V

FAMILY	ITEM#	WATTAGE	LIGHT COLOR	CCT	BEAM	LUMENS	FINISH	DRIVER	INPUT VOLTAGE
ENNEN	D10107UVW	20W	Daylight - Cool White - Warm White	6000K - 4000K - 3000K	100°	1500lm	WHITE	0-10V	120V - 277V

866.356.4458
solavantilighting.com

Intertek | LED BUILT IN | 80 CRI | 8.26" | 3.15" ceiling depth | 100°

D10130UV | 30W | SMD LED | *UGR19 Fixed Recessed Downlight w/ Adjustable CCT*

IP44



Remote Driver Enclosure = 6" x 10" x 2"
w/10' Standard Connecting Cable



0-10V dimming option, available for 277V

FAMILY	ITEM#	WATTAGE	LIGHT COLOR	CCT	BEAM	LUMENS	FINISH	DRIVER	INPUT VOLTAGE
ENNEN	D10107UVW	30W	Daylight - Cool White - Warm White	6000K - 4000K - 3000K	100°	2250lm	WHITE	0-10V	120V - 277V